



# J - RANGE

*Forced Draft Dry Cooler*



*Technology for the Future  
Available Today*



**Flex Coil a/s**  
Knøsgårdvej 115 | DK-9440 Aabybro  
Tel.: +45 98 24 49 99 | Fax +45 98 24 49 90  
e-mail: [flexcoil@flexcoil.dk](mailto:flexcoil@flexcoil.dk) | web: [www.flexcoil.dk](http://www.flexcoil.dk)





# J - RANGE

*Forced Draft Dry Cooler*



The New J - Range of Forced Draft Dry Coolers offers a welcome expansion to the Flex coil product line. Also available in both horizontal or vertical orientation

Standard induced draft dry coolers require leaving air temperatures below 70 deg C to ensure motor longevity and prevent motor overheating.



The forced draft arrangement inherently allows for the lower ambient air temperature to pass over the motor preventing overheating whilst increasing the air mass flow rate, thus improving thermal performance.

The New J - Range is available with the FlexShield Corrosion Protection System array of material choices



**Flex Coil a/s**

Knøsgårdvej 115 | DK-9440 Aabybro  
Tel.: +45 98 24 49 99 | Fax +45 98 24 49 90  
e-mail: flexcoil@flexcoil.dk | web: www.flexcoil.dk

Scan the code, and get the latest version of this or any other Flex coil catalog

